



## SAFETY DATA SHEET

EASY CLEAN

Page 1

Issued: 29/01/2009

Revision No: 3

### 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

**Product name:** EASY CLEAN

**Company name:** Advanced Engineering Ltd

Guardian House

Stroudley Road

Basingstoke

Hampshire

RG24 8NL

United Kingdom

Tel: +44(0)1256460300

Fax: +44(0)1256462266

Emergency tel: +44(0)1256854318

Email: sales@advancedengineering.co.uk

### 2. HAZARDS IDENTIFICATION

**Main hazards:** Extremely flammable.

**Other hazards:** Heating may cause an explosion.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

**Hazardous ingredients:** PROPANE 1-10%

EINECS: 200-827-9 CAS: 74-98-6

[F+] R12

- BUTANE 1-10%

EINECS: 203-448-7 CAS: 106-97-8

[F+] R12

- 3-BUTOXYPROPAN-2-OL 1-10%

EINECS: 225-878-4 CAS: 5131-66-8

[Xi] R36/38

- 2-AMINOETHANOL 1-10%

EINECS: 205-483-3 CAS: 141-43-5

[Xn] R20/21/22; [C] R34

- 1-METHOXY-2-PROPANOL 10-30%

EINECS: 203-539-1 CAS: 107-98-2

[-] R10

### 4. FIRST AID MEASURES (SYMPTOMS)

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** It is unlikely that this substance will be swallowed due to its physical properties.

[cont...]

**SAFETY DATA SHEET**

EASY CLEAN

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing. Nausea and stomach pain may occur.

**4. FIRST AID MEASURES (ACTION)**

**Skin contact:** Wash immediately with plenty of soap and water. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. Transfer to hospital as soon as possible.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious, check for breathing and apply artificial respiration if necessary. Transfer to hospital as soon as possible.

**5. FIRE-FIGHTING MEASURES**

**Extinguishing media:** Alcohol or polymer foam. Water fog. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

**Exposure hazards:** Extremely flammable. Vapour may travel considerable distance to source of ignition and flash back. Forms explosive air-vapour mixture.

**Protection of fire-fighters:** Wear self-contained breathing apparatus.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions:** Eliminate all sources of ignition.

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

**7. HANDLING AND STORAGE**

**Handling requirements:** Ensure there is sufficient ventilation of the area. Smoking is forbidden. Do not handle in a confined space.

**Storage conditions:** Store in cool, well ventilated area. Avoid incompatible materials and conditions - see section 10 of SDS.

**Suitable packaging:** Must only be kept in original packaging.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Hazardous ingredients:** BUTANE

WEL (8 hr TWA): 1450 mg/m<sup>3</sup> WEL (15 min STEL): 1810 mg/m<sup>3</sup>

- 2-AMINOETHANOL

WEL (8 hr TWA): 2.5 mg/m<sup>3</sup> WEL (15 min STEL): 7.6 mg/m<sup>3</sup>

- 1-METHOXY-2-PROPANOL

WEL (8 hr TWA): 375 mg/m<sup>3</sup> WEL (15 min STEL): 560 mg/m<sup>3</sup>

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Gas/vapour filter, type A: organic vapours (EN141).

**Hand protection:** Impermeable gloves.

**Eye protection:** Face-shield.

**Skin protection:** Protective clothing, PVC.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**State:** Aerosol

**Colour:** Colourless

**Odour:** Characteristic odour

**Evaporation rate:** Moderate

**Flammability limits %: lower:** 1.8

**upper:** 9.5

**Flash point°C:** -40

**Autoflammability°C:** 410 - 580

## 10. STABILITY AND REACTIVITY

**Stability:** Stable under normal conditions.

**Conditions to avoid:** Sources of ignition. Heat. Flames.

**Haz. decomp. products:** In combustion emits toxic fumes.

## 11. TOXICOLOGICAL INFORMATION

**Hazardous ingredients:** 3-BUTOXYPROPAN-2-OL

ORL RAT LD50 5660 µl/kg

SKN RBT LD50 3100 mg/kg

• 2-AMINOETHANOL

IVN RAT LD50 225 mg/kg

ORL MUS LD50 700 mg/kg

ORL RAT LD50 1720 mg/kg

SCU RAT LD50 1500 mg/kg

• 1-METHOXY-2-PROPANOL

IVN RAT LD50 4200 mg/kg

ORL MUS LD50 11700 mg/kg

ORL RAT LDLO 3739 mg/kg

**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

## 12. ECOLOGICAL INFORMATION

**Mobility:** Volatile.

**Persistence and degradability:** No data available.

**Bioaccumulative potential:** No bioaccumulation potential.

**Other adverse effects:** Negligible ecotoxicity.

**13. DISPOSAL CONSIDERATIONS**

**Disposal of packaging:** Dispose of as normal industrial waste.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**14. TRANSPORT INFORMATION****ADR / RID**

**UN no:** 1950

**ADR Class:** 2

**Classification code:** 5F

**Shipping name:** AEROSOLS (BUTANE)

**Labelling:** 2.1

**IMDG / IMO**

**UN no:** 1950

**Class:** 2

**EmS:** F-D,S-U

**Marine pollutant:** .

**Labelling:** 2.1

**IATA / ICAO**

**UN no:** 1950

**Class:** 2

**Labelling:** 2.1

**15. REGULATORY INFORMATION**

**Hazard symbols:** Extremely flammable.



**Risk phrases:** R12: Extremely flammable.

**Safety phrases:** S1/2: Keep locked up and out of the reach of children.

S16: Keep away from sources of ignition - No smoking.

S38: In case of insufficient ventilation, wear suitable respiratory equipment.

S51: Use only in well-ventilated areas.

S23: Do not breathe spray.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

**Precautionary phrases:** Pressurized container: protect from sunlight and do not expose to temperatures exceeding

## SAFETY DATA SHEET

EASY CLEAN

50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

### 16. OTHER INFORMATION

**Risk phrases used in s.3:** R12: Extremely flammable.

R36/38: Irritating to eyes and skin.

R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.

R34: Causes burns.

R10: Flammable.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.